



Thermafiber® RainBarrier® HD Mineral Wool Insulation



Description

Thermafiber® RainBarrier® HD is a high density board with a consistent 6.0 pcf density throughout the entire thickness of the product. The consistent density from top to bottom helps eliminate the need to orient the piece in a certain direction. Thermafiber® RainBarrier® HD continuous insulation products are designed for exceptional performance in rain screen and cavity wall construction applications. Mineral wool insulation provides thermal insulation, fire resistive characteristics, and acoustical control while efficiently draining water from a cavity system. All Thermafiber® RainBarrier® products are non-combustible and compatible with common wall ties and air barrier systems.

Standards, Codes Compliance

ASTM C 665	Non-corrosive
ASTM C 795	Pass
ASTM C 612	RainBarrier® HD Type IA, IB, II, III, IVA
ASTM E 136	Non-combustible as defined per NFPA Standard 220
CAN/ULC S114	Complies
ASTM E 96	Unfaced, 50 Perms as tested
ASTM E 84	Flame Spread 0, Smoke Developed 0
CAN/ULC S 102	Flame Spread 0, Smoke Developed 5
ASTM C 1104	Absorbs 0.03% by volume
ASTM C 356	Linear Shrinkage <2% 1200° F (650° C)

Product Options

Recycled Content Option^{1,2}:

EPA Choice Fiber
(US Government Buildings) Minimum 75%

Standard Fiber 70%

1. Recycled content options other than standard must be specified at time of order.

Technical Data

Actual Density	Tested to ASTM C 518		Tested to ASTM E 84 Unfaced	
	"k" @ 75° [24°C] BTU.in/hr .sq. ft. °F	"R" value per inch of thickness***	Flame Spread	Smoke Developed
6.0 pcf	0.23	4.3	0	0

***R = thickness divided by 'k'

Acoustical Performance

Thickness	Coefficients at Frequencies Per ASTM C 423						
	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	NRC
2"	0.36	0.79	1.15	1.04	1.01	1.04	1.00
4"	1.15	1.17	1.18	1.03	1.06	1.08	1.10
6"	1.18	1.01	1.11	1.03	1.06	1.10	1.05

Installation

Thermafiber, Inc. recommends mechanical attachment of Thermafiber® RainBarrier® insulation products. See Owens Corning publication "Thermafiber® RainBarrier® Insulation Installation Guide" (Pub. No. 10021141) for more information.

Availability

Thickness*	Widths**	Lengths**
1" - 7"	16", 24", 36"	48", 60"

* Thicknesses are available in 1/2" increments.

** Custom sizes are available upon request.

Thermafiber Insolutions®

Thermafiber Insolutions® offers industry leading technical and engineering assistance to architects, specifiers, and contractors. These services include CAD drawings, engineering judgments, LEED® Credit Information, and product recommendations. Contact our technical services department at 1-888-834-2371 or email ThermafiberInsolutions@owenscorning.com.

Features

- Non-combustible, non-deteriorating, and inorganic
- Repels and efficiently drains water heavy density rigid board
- Helps conserve energy, reduce greenhouse gas emissions
- Fire resistant to temperatures above 2,000° F (1,093° C)
- Enhances acoustical performance
- Minimum 70% recycled content²
- Contributes to credits in several green building programs such as LEED® and Green Globes®

Environmental and Sustainability

Owens Corning is a worldwide leader in building material systems, insulation and composite solutions, delivering a broad range of high quality products and services. Owens Corning is committed to driving sustainability by delivering solutions, transforming markets and enhancing lives. More information can be found at www.owenscorning.com.

Notes

For additional information refer to the Safe Use Instruction Sheet (SUIS) found in the SDS Database via <http://sds.owenscorning.com>.

Submittal Approvals


Job Name _____

Contractor _____

Date _____



Made in the USA



Thermafiber® RainBarrier® HD continuous insulation was installed in the Wisconsin Institute for Discovery in Madison, WI and helped contribute to its LEED® Gold rating.

Certifications and Sustainable Features

- ²Verified by ICC-ES to contain a minimum of 70% recycled content. See ICC-ES Evaluation Report VAR-1025 at icc-es.org.
- Environmental Product Declaration (EPD) has been certified by UL Environment. For more information visit ul.com/epd.
- Material Health Certificate from Cradle to Cradle Products Innovation Institute. For more information visit c2ccertified.org.



Disclaimer of Liability

Thermafiber, Inc. shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Thermafiber, Inc. liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing within thirty (30) days from date it was or reasonably should have been discovered.

LEED® is a registered trademark of the U.S. Green Building Council.
Green Globes® is a registered trademark of Green Building Initiative, Inc.

THERMAFIBER, INC.
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659
888-TFIBER1 [834-2371]
www.thermafiber.com

Pub. No. 10021140-D formerly TF524. Printed in U.S.A. July 2017.
THE PINK PANTHER™ & © 1964–2017 Metro-Goldwyn-Mayer Studios Inc.
All Rights Reserved. The color PINK is a registered trademark of Owens Corning.
© 2017 Owens Corning. All Rights Reserved. © 2017 Thermafiber, Inc.
All Rights Reserved.

