



DESCRIPTION

Griffolyn® Type-65 is a 3-ply laminate combining two layers of high-density polyethylene and a high-strength cord grid. The non-woven cord grid provides a uniform loading resistance. It is specifically engineered to provide high strength and durability in a lightweight material.

PHYSICAL PROPERTIES AND TYPICAL VALUES

PROPERTY	ASTM TEST METHOD	U.S. VALUE	METRIC VALUE
Weight	D-751	41.5 LB/1000 FT ²	20.3 KG/100 M ²
3" Tensile Strength	D-882	140 LBF	6637 N
Puncture Strength	D-4833	55 LBF	245 N
PPT Resistance	D-2582	42 LBF	187 N
Dart Impact Strength	D-1709	1.25 LBS	570 g
Cold Impact Strength	D-1790	-40°F	-40°C
Permeance	E-96	0.038 Grain/Hr•Ft ² •In.Hg	2.18 NG/(PA•S•M ²)

Class C, ASTM E-1745-11 Standard Specification for Water Vapor Retarders Used in Contact With Soil or Granular Fill Under Concrete Slabs.

FEATURES AND BENEFITS

- Multiple layers and cord reinforcement resists tears.
- UV stabilization protects the material from degradation during extended exposure to sunlight.
- Cold-crack resistance eliminates failures in extremely cold temperatures.
- Chemically resistant to withstand exposure without significant deterioration.
- Low permeability greatly inhibits moisture transmission.
- Flexibility and light weight allow for easy handling and quick installation.
- Custom fabrication is available to meet your exact specifications.
- High durability allows for significant savings through reuse and fewer replacements.

MORE ▶▶

OUR CUSTOMERS DON'T JUST *cover their business,*
▶ THEY PROTECT IT



SUGGESTED APPLICATIONS

- Architectural vapor retarder for underslab, in walls & ceilings and in roofing systems.
- Pallet, cable reel and drum covers for outside storage.
- Floor covers, dust partitions and cleanroom enclosures.
- Temporary walls, plant dividers, building enclosures and containment tents.
- Shipping container covers and liners.
- Soil covers to control leachate for stockpiles and landfills.
- Erosion control and slope protection covers.

ORDERING INFORMATION

AVAILABLE COLORS:

Black

SIZES:

Rolls are available from 4' x 100' to 40' x 100' in increments of 4' widths. Some sizes available for immediate shipment. Standard length and width tolerances are $\pm 1\%$ (minimum 2")

Custom sizes up to 120' x 200' and custom fabrication are available to meet your exact specifications.

USABLE TEMPERATURE RANGE:

Minimum: -25°F -31.6°C

Maximum: 170°F 77°C

OUTDOOR EXPOSURE

Under normal continuous exposure the average life expectancy ranges from 18 to 30 months, depending on color.